

Technical data

| | |
|-------------------------------|-------------------|
| Rated voltage | 230V AC |
| Input voltage range | 120 - 277 V AC |
| Class | 1 |
| IP | 65 |
| IK | 10 |
| Diffuser | Satin-finish PMMA |
| Bulb cover | No |
| Source | Built-in LED |
| Color temperature real output | 3000°K warm white |
| Real light output | 1952 lm |
| Total consumption | 26 W |
| Energy class | C (Source LED) |
| IRC | >80 |
| SDCM | 4 |
| Dimmable | No |
| Ta | - |
| Ambient temperature range | -10 ~50°C |
| UGR | - |
| ULR | - |
| Photobiological Risk group | RG2 |
| Fixing kit | Yes |
| With sensor | No |
| With IP55 socket | No |

[Download the installation manual](#)



Materials and finishes

| | |
|----------|----------------------------|
| Material | aluminium |
| Colour | Jet black - 000 - RAL 9005 |

Logistic data

| | |
|----------------------|-------------------|
| Product dimensions | H.400 L.260 P.183 |
| Net weight | 2.930 Kg |
| Gross weight | 3.620 Kg |
| Package dimensions 1 | H.470 L.350 P.200 |

Certifications and warranties

| | |
|----------------|-------------------------|
| CE | Yes |
| UL | No |
| EAC | Yes |
| RoHS | Yes |
| ENEC | No |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical | 5 years |
| Electronics | 5 years |